

# C1.SOAP-E

**Cleaner for epoxy grouting**

## MATERIALS

- Marble
- Granite
- Natural stone
- Recomposed
- Ceramic
- Stoneware
- Klinker

## APPLICATION FIELDS

- Floorings
- Stairs
- Coverings



## CHARACTERISTICS

- Water-based
- It removes residues and halos of epoxy stucco
- Ideal for cleaning of end-laying
- It does not damage the surfaces and the joints
- Easy to use

## INSTRUCTION

### SHAKE BEFORE USING

Ready to use product. Pour C1.SOAP-E onto the surface. Let it react for 5-30 minutes, depending from the quantity of stucco to remove, from the laying time and surface's absorbment. Rub it with a white pad like the scotch brite. At the end draw with a wet-vacuum or clean with wet cloth. Rinse. Let it dry before stepping the surface.

## PACKAGING

- Box of 16 Pcs of 1 Lt/Kg
- Box of 8 Pcs of 2 Lts/Kgs
- Box of 4 Pcs of 5 Lts/Kgs
- Tank of 25 Lts/Kgs

## COVERAGE

Approximate coverage: 1 lt x 10 - 20 m2  
Depending on the surface to be clean

## WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about the suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.