

F5.12 LINE

Liquid wax for waxing machines for polished surfaces

MATERIALS

- Marble
- Granite
- Natural stone
- Recomposed

APPLICATION FIELDS

- Slabs



CHARACTERISTICS

- Solvent based
- Excellent polishing power
- Very high coverage
- Gives some colour
- Industrial application
- Excellent water-repellent
- It does not turn yellow over time

INSTRUCTION

SHAKE BEFORE USING

Ready to use product. On clean and dry surfaces apply F5.12 LINE spread it uniformly with polisher or slab polisher. On low level absorbent surfaces it may result a light residue that will be easily eliminated rubbing it with a microfibre cloth or white pad like the scotch brite.

PACKAGING

- Box of 4 Pcs of 5 Lts/Kgs
- Tank 25 Lts/Kgs

COVERAGE

Approximate coverage: 1 lt x 20 - 40 m2
Depending on the surface to be treated

WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about The suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.