

# F5.2R

Lightly satin finish protective against acidic substances for smoothed and brushed surfaces

## MATERIALS

- Marble
- Granite
- Natural stone
- Beton/Cement

## APPLICATION FIELDS

- Coverings
- Kitchen Countertops
- Bathroom Countertops
- Tables



## CHARACTERISTICS

- Water based
- Satin finishing for smoothed and brushed surfaces
- Cover the superficial porosity
- Facilitates the cleaning
- Excellent water-repellent
- Create a very light invisible film thus separating the surface from direct contact with acidic agents allowing you to clean within a few minutes
- It does not turn yellow over time

## INSTRUCTION

### SHAKE BEFORE USING

Ready to use product.

Application on clean, dry and not previously treated surfaces. Use the microfiber cloth (available in the catalog in the accessories section). Moisten the microfiber cloth with F5.2R. Pour a small amount of product on the surface and spread it evenly with the damp cloth. It is recommended apply more coats, so as to create a good film, pouring each time very little product so as to spread it well and let it dry evenly with each coat. The product will be dry after a few hours and ready for use after a few days. We recommend use the C1.07 DAY neutral ready to use detergent for routine cleaning with microfiber cloth, no sponges and abrasive scouring pads.

## PACKAGING

- Box of 20 Pcs of 0,5 Lt/Kg
- Box of 16 Pcs of 1 Lt/Kg
- Box of 8 Pcs of 2 Lts/Kgs
- Box of 4 Pcs of 5 Lts/Kgs

## COVERAGE

Approximate coverage: 1 lt x 25 - 35 m2  
Depending on the surface to be treated

## WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about The suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.