

M7.80

Liquid flocculant in emulsion

FUNCTION

- Water treatment

APPLICATION FIELDS

- Sedimentation sacks
- Water treatment plants



CHARACTERISTICS

- Easy to disperse in water
- Does not form lumps
- Does not create problems of clogging in pumps
- Effective in both neutral and alkaline fields
- Effective for the abatement of solid particles suspended in water used in the processing of stone materials
- Can be used in small and large clarification plants and decanting tanks

INSTRUCTION

SHAKE BEFORE USING

WATER TREATMENT PLANTS

Pour M7.80 into the preparation tank of the flocculant in the percentage of 1 kg in 1.000 liters of clean water.

SEDIMENTATION SACKS

Use a plastic tank of 25 kg with tap and mix 3/5 kg of M7.80 in 20 liters of clean water.

PACKAGING

- Tank 25 Lts/Kgs

WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about the suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.