

# M7.83

**PH corrector +**

## FUNCTION

- Water treatment

## APPLICATION FIELDS

- Water treatment plants



## CHARACTERISTICS

- Increases and stabilizes the PH of the water
- Regresses oxidation by blocking corrosion
- Eliminates acidity of water
- Restores the conditions for the maintenance in perfect condition of all equipment

## INSTRUCTION

### SHAKE BEFORE USING

Ready to use product.

Pour M7.83, where is possible, on closed circuit water system up to PH 9,5 approximately. It is recommended to use automatic measuring and dosing systems with PH reading and adjustment. Keep the value constant by feeding the circuit with M7.83 by keeping it controlled with the help of a meter or litmus paper.

## PACKAGING

- Tank of 25 Lts/Kgs

## WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about the suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.