

M7.84

PH corrector -

FUNCTION

- Water treatment

APPLICATION FIELDS

- Water treatment plants
- Sedimentation sacks



CHARACTERISTICS

- Decreases and stabilizes the PH of the water
- Aggregates suspended particles in recycled water
- Necessary when in waste water the values exceed the limits allowed by law
- Restores the conditions for the maintenance in perfect condition of all equipment

INSTRUCTION

SHAKE BEFORE USING

Ready to use product.

WATER TREATMENT PLANTS

M7.84 shall not be mixed in the preparation tank of the flocculant but inserted upstream, for example in the collection well waste water. Indispensable to act for 20/30 seconds before the flocculation.

SEDIMENTATION SACKS

Use a 35 kg plastic drum with tap and mix about 10 kg of M7.84 in 20/25 liters of clean water.

PACKAGING

- Tank of 25 Lts/Kgs

WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about the suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.