

M7.86

Lubrificant protective for machinery maintenance

FUNCTION

- Machinery maintenance

APPLICATION FIELDS

- Machinery



CHARACTERISTICS

- Protective lubricant for all types of machinery used in marble and granite processing
- It adheres and protects the painted steel parts, the bolting, etc...
- Dust and mud residues will adhere minimally making cleaning much easier
- Forms a protective barrier against sludge, alkaline vapours, acids and oxidation and corrosion phenomena
- To be used for machines such as polishing machines, milling machines, roller conveyors, etc..

INSTRUCTION

SHAKE BEFORE USING

Ready to use product.

On clean surfaces, cleaned with M7.85, spray uniformly M7.86. We recommend at least 2 treatments per month to better preserve the machinery.

PACKAGING

- Tank of 5 Lts/Kgs
- Tank of 25 Lts/Kgs

WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about the suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.