

P.E.3 ANTIQUE

Acid treatment with antique effect for marbles and calcium based stones



MATERIALS

- Marble
- Calcium based stones

APPLICATION FIELDS

- Floorings
- Stairs
- Slabs



CHARACTERISTICS

- Acid based
- Superficial corrector
- Lived and antiqued effect
- More or less deep porosity depending on the processing time of the product and the type of material treated
- Modifies the superficial finishes of the materials with a lot of calcium carbonate
- Efficient on materials as Rosso Verona, Biancone, Travertino, Trani, Crema Marfil, Rosso Alicante, ect...
- Gives a new life to materials changing the originary finishes
- Particularily suitable to make a fast and easy work in alternative to mechanic work
- Diluted eliminates the classic whitening of marble

INSTRUCTION

SHAKE BEFORE USING

Only for open workspace.
Ready to use product.

On clean and dry surfaces pour P.E.3. ANTIQUE uniformly with a plastic watering can. There will be an effervescent reaction under form of the foam. Let it react for 2-5 minutes until the foam subsided. Don't let it dry on the surface. Rinse with abundant water. Repeat it to obtain more rough effect.

PACKAGING

- Box of 12 Pcs of 1 Lt/Kg
- Box of 4 Pcs of 5 Lts/Kgs
- Tank of 13 Lts/Kgs
- Tank of 25 Lts/Kgs

COVERAGE

Approximate coverage: 1 lt x 2 - 3 m²
Depending on the surface to be treated

WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about The suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.