# T3.19 CONSOLIDO

## Consolidating impregnating treatment for low compact materials

### **MATERIALS**

- Marble
- Sandstone
- Natural Stone
- Beton/Cement
- Granite

#### **APPLICATION FIELDS**

- Floorings
- Stairs
- Coverings
- Facades
- Window sills
- Monuments
- Statues



## **CHARACTERISTICS**

- Solvent based
- It could slightly change the colour of the surface
- Excellent water-repellent
- Impregnating with complete absorption
- Permanently modifies the porosity
- Increases consistency and hardens the surface
- It leaves the surfaces breathable
- It is possible apply after of it a anti-stain treatment T3.11 or wet-effect T3.15
- It does not turn yellow over time
- Resistant to high pedestrian traffic
- Resists the aggressive action of atmospheric agents

## **INSTRUCTION**

#### SHAKE BEFORE USING

Ready to use product. On clean and dry surfaces apply T3.19 CONSOLIDO spread it uniformly with a brush making cross coats or with microfibre cloth. Depending on the absorbment of the surface apply the second coat just after the first. On low level absorbent surfaces it may result a light residue that will be easily eliminated before that it begincompletely drying rubbing it with a microfibre cloth or white pad like the scotch brite.

## **PACKAGING**

- Box of 12 Pcs of 1 Lt/Kg
- Box of 8 Pcs of 2 Lts/Kgs
- Box of 4 Pcs of 5 Lts/Kgs
- Tank of 25 Lts/Kgs

## **COVERAGE**

Approximate coverage: 1 lt x 8 - 15 m2 Depending on the surface to be treated Coverage shown is refers to single coats

#### WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about The suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.

