# T3.512

# **Consolidator water-repellent for beton surfaces**

#### **MATERIALS**

- Beton
- Microcement
- Industrial Floors
- Grit of marble and concrete
- Venetian paving
- Terrazzo

#### **APPLICATION FIELDS**

- Flooring
- Stairs
- Coverings



## **CHARACTERISTICS**

- Solvent based
- It could slightly change the colour of the surface
- It gives the surface a natural effect
- Excellent water-repellent with complete absorption
- Hardens the surface and permanently modifies the porosity allowing the possible subsequent application of anti-stain treatment like T3.11 or wet-effect treatment like T3.15
- It leaves the surfaces breathable
- It does not turn yellow over time
- Resistant to high pedestrian traffic
- Prevents the formation of absorption stains

# **INSTRUCTION**

SHAKE BEFORE USING

Ready to use product.

On clean surfaces apply T3.512 spread it uniformly with a brush making cross coats or spraying it with nebulizer. Depending on the absorbment of the surface apply the second coat just after the first.

### **PACKAGING**

- Box of 20 Pcs of 0,5 Lt/Kg
- Box of 12 Pcs of 1 Lt/Kg
- Box of 8 Pcs of 2 Lts/Kgs
- Box of 4 Pcs of 5 Lts/Kgs
- Tank of 25 Lts/Kgs

## **COVERAGE**

Approximate coverage: 1 lt x 8 - 15 m2 Depending on the surface to be treated

#### WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about The suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.

