

T3.512H

Consolidating treatment without solvent with silicates for polished beton

MATERIALS

- Industrial Floors
- Beton/Cement
- Grit of marble and concrete
- Venetian paving
- Terrazzo
- Soft Limestone
- Microcement

APPLICATION FIELDS

- Floorings
- Stairs



CHARACTERISTICS

- Water based
- It contain silicates
- It gives the surface a natural effect
- Excellent water-repellent with complete absorption
- It leaves the surfaces breathable
- It does not turn yellow over time
- Resistant to high pedestrian traffic
- It gives the beton/cement surfaces easy for polish with XShine grit 800
- On treated support can be applicated the water-repellent without solvent T3.02H

INSTRUCTION

SHAKE BEFORE USING

Ready to use product. Do not apply on hot or sunny surfaces. The temperature of the surfaces to be treated should be between +5°C and +35 °C. On clean, cold and dry surfaces apply T3.512H spread it uniformly with a brush making cross coats or spraying it with nebulizer. Depending on the absorbment of the surface apply the second coat just after the first.

The consolidation complete of the product will be only at complete drying of it. It can ask many days depending of temperature.

PACKAGING

- Box of 16 Pcs of 1 Lt/Kg
- Box of 8 Pcs of 2 Lts/Kgs
- Box of 4 Pcs of 5 Lts/Kgs
- Tank of 25 Lts/Kgs

COVERAGE

Approximate coverage: 1 lt x 14 - 20 m2
Depending on the surface to be treated
Coverage shown is refers to single coats

WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about The suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.