# **T3.TERRACE CARE**

# Water-proofing consolidating for terraces

#### **MATERIALS**

- Marble
- Granite
- Natural stone
- Porcelain tiles
- Beton
- Terracotta
- Quarry tiles
- Tuff

#### **APPLICATION FIELDS**

- Outdoor floorings
- Balconies
- Terraces
- Shower trays



On clean and dry surfaces apply T3.TERRACE CARE spread it

uniformly with a brush on all the surface, particularly on joints

and fissures. Depending on the absorbment of the surface apply

#### **CHARACTERISTICS**

- Solvent based
- It does not change the colour of the surface
- It gives the surface a natural effect
- It leaves no residue on the surface
- Protects joints and cracks and prevents the formation of moulds and efflorescences and serious structural damage
- Excellent water-repellent
- It does not create unsightly films
- Water-proofing breathable consolidating
- Penetrates into materials strengthening the surface
- Removes any water seepage problem
- It does not turn yellow over time
- Easy to apply

INSTRUCTION

SHAKE BEFORE USING

Ready to use product.

the second coat just after the first.

### COVERAGE

Approximate coverage: 1 lt x 5 - 6 m2 Depending on the surface to be treated

#### **PACKAGING**

- Box of 12 Pcs of 1 Lt/Kg
- Box of 8 Pcs of 2 Lts/Kgs
- Box of 4 Pcs of 5 Lts/Kgs

## WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about The suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.

