

# C1.09

## Wax remover water based

### MATERIALS

- Marble
- Granite
- Natural stone
- Recomposed
- Ceramic
- Stoneware
- Beton
- Terracotta
- Klinker

### APPLICATION FIELDS

- Floorings
- Stairs
- Coverings
- Kitchen Countertops
- Bathroom Countertops
- Tables



### CHARACTERISTICS

- Detergent ph 9
- Wax remover water based
- Remove polishing, water-based, synthetic and natural waxes
- Ideal to remove old waxes from marbles, granites, stones, terracotta
- Does not damage the delicate surfaces
- Easy to use
- Ideal for all surfaces and finishes

### INSTRUCTION

#### SHAKE BEFORE USING

Dilute in water 1:2 - 1:10

Pour C1.09 diluted onto the surface. Spread it uniformly proceeding on small areas step by step. Let it react for 10 minutes. Manual cleaning: rub it with a scrubber. Mechanical cleaning: use a monobrush with its scrubber. At the end draw with a wet-vacuum or clean with wet cloth. Rinse. Let it dry before stepping the surface. Use C1.09 diluted in hot water until to 1:2 for a more waxed floor, before test it.

### PACKAGING

- Box of 20 Pcs of 0,5 Lt/Kg
- Box of 16 Pcs of 1 Lt/Kg
- Box of 8 Pcs of 2 Lts/Kgs
- Box of 4 Pcs of 5 Lts/Kgs
- Tank of 25 Lts/Kgs

### COVERAGE

Approximate coverage: 1 lt x 10 - 15 m2  
Depending on the surface to be clean

### WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about the suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.