

F5.2A

Satin finish protective against acidic substances for smoothed and brushed surfaces

MATERIALS

- Marble
- Granite
- Natural stone
- Beton/Cement

APPLICATION FIELDS

- Flooring
- Coverings
- Kitchen Countertops
- Bathroom Countertops
- Tables



CHARACTERISTICS

- Solvent based
- Satin finishing for smoothed and brushed surfaces
- Cover the superficial porosity
- Facilitates the cleaning
- Excellent water-repellent
- Create a lot resistant film thus separating the surface from direct contact with acidic agents allowing you to clean within a few hours
- It does not turn yellow over time

INSTRUCTION

SHAKE BEFORE USING

Ready to use product.

Application on clean, dry and not previously treated surfaces. Use a short pile roller. Pour F5.2A on the surface and spread it in cross verses to cover the entire surface. On very uneven surfaces it is possible to apply a second coat to be sure to cover the entire surface well. The product will be dry after a few hours and ready for use after a few days. It is recommended to use the ready to use neutral detergent C1.07 DAY for ordinary cleaning with microfiber cloth, no sponges and abrasive scouring pads.

PACKAGING

- Box of 20 Pcs of 0,5 Lt/Kg
- Box of 12 Pcs of 1 Lt/Kg
- Box of 8 Pcs of 2 Lts/Kgs
- Box of 4 Pcs of 5 Lts/Kgs

COVERAGE

Approximate coverage: 1 lt x 8 - 20 m²
Depending on the surface to be treated

WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about The suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.