

M7.81

Killing and control foam

FUNCTION

- Water treatment

APPLICATION FIELDS

- Water treatment plants



CHARACTERISTICS

- Anti-foam in emulsion
- Quickly abates the foam generated by the processing of resins
- Effective in both neutral and alkaline fields
- Effective in cationic or anionic environments
- Successfully employed in the purification of the waters of the stone sector
- Indicated in case of residues of polyester, acrylic and epoxy resins

INSTRUCTION

SHAKE BEFORE USING

Ready to use product.

Pour M7.81, where is possible, on closed circuit water system where it may come in most contact with the foam.

PACKAGING

- Tank of 25 Lts/Kgs

WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about the suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.