

# PROTECT POOL-P

Anti-corrosion treatment for polished pools

## MATERIALS

- Marble
- Granite
- Natural stone

## APPLICATION FIELDS

- Pools
- Fountains

## CHARACTERISTICS

- Solvent based
- Professional use
- Anti-corrosion for polished pools
- Create an invisible film that separates the surface from direct contact with water
- Prevents that the surface will be corroding, flaking, whitening from water
- It does not turn yellow over time

## NOTE

The PROTECT POOL can only be applied on perfectly installed and tightly sealed coverings. There must be no infiltration and no water pushes from the back of the tile. The product can only be applied on perfectly dry surfaces. The PROTECT POOL is a film and will tend to skin if there is pushed of water and infiltration from the back.

## PACKAGING

- Box of 6 Pcs composed of 0,5 + 0,5 Lt/Kg

## WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about The suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.



## INSTRUCTION

### SHAKE BEFORE USING

Pour SOLVENT PP-P into the bottle of PROTECT POOL-P, mix it and shake it well. Read the instructions of PROTECT POOL-P. Apply to a temperature not less than 10°.

Use it immediately after mixing it. On clean and dry surfaces pour onto supplied tray PROTECT POOL-P, just mixed with SOLVENT PP-P and shake it well. Spread it uniformly with supplied roller making cross coats and light pressure.

Depending on the temperature, let it dry completely and apply the second coat.

## COVERAGE

Approximate coverage: 1 lt x 10 - 15 m2

Depending on the surface to be treated

Coverage shown is refers to single coats