

# T3.62H

Impregnating without solvent for terracotta surfaces

## MATERIALS

- Terracotta
- Brick
- Tuff
- Klinker

## APPLICATION FIELDS

- Floorings
- Stairs
- Coverings
- Facades
- Window sills



## CHARACTERISTICS

- Water based
- It does not change the colour of the surface
- It gives the surface a natural effect
- It leaves no residue on the surface
- Prevents the formation of absorption stains
- Limits problems caused by rain, damp, mold, etc...
- Water-repellent with complete absorption
- Suitable for all surfaces in terracotta, exposed brick, tuff
- Easy to apply
- It does not turn yellow over time
- Attention: it does not protect against acid substances

## INSTRUCTION

### SHAKE BEFORE USING

Ready to use product. On clean and dry surfaces apply T3.62H spread it uniformly with a brush making cross coats or spraying it with nebulizer. Depending on the absorbment of the surface apply the second coat just after the first.

To complete the working cycle it is recommended to apply subsequently the product F5.63 which will thus make the surface anti-stain and anti-dirt.

## PACKAGING

- Box of 20 Pcs of 0,5 Lt/Kg
- Box of 16 Pcs of 1 Lt/Kg
- Box of 8 Pcs of 2 Lts/Kgs
- Box of 4 Pcs of 5 Lts/Kgs
- Tank of 25 Lts/Kgs

## COVERAGE

Approximate coverage: 1 lt x 6 - 8 m2  
Depending on the surface to be treated

## WARNINGS

Apply at an ambient temperature between 10°C - 20°C. Keep out of reach of children. Do not disperse into the environment. Before use, consult the safety data sheet and label, in which risks and safety are highlighted for the correct use of personal protective equipment. All information contained in this page is based on information we believe to be reliable; however, not knowing the conditions of the materials treated and the way you use the product, ITALIAN XS declines all responsibility about The suitability of the material for each particular application. Store the product in the original containers and hermetically closed. Store the product at a temperature between 5° C - 20° C. If stored as indicated above, the product has a shelf life of 12 months. It is advisable to carry out preventive tests on small areas as our responsibility is limited at the cost of the product. No liability for damage caused by negligence or misuse of the product.